




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16D 65/16, F16H 25/22, 61/38, B60T 13/74		A1	(11) International Publication Number: WO 99/60285
			(43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/NL99/00303		(74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).	
(22) International Filing Date: 18 May 1999 (18.05.99)			
(30) Priority Data: 1009197 18 May 1998 (18.05.98) NL		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71) Applicant (for all designated States except US): SKF ENGINEERING & RESEARCH CENTRE B.V. [NL/NL]; P.O. Box 2350, NL-3430 DT Nieuwegein (NL).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): OLSCHIEWSKI, Armin, Herbert, Emil, August [DE/NL]; Nedereindseweg 121, NL-3438 AC Nieuwegein (NL). KAPAAN, Henrikus, Jan [NL/NL]; Waterhoen 5, NL-3435 DM Nieuwegein (NL). DRUET, Clair [FR/FR]; 283, route la Carnalaz, F-73420 Drumettaz Clarafond (FR). FUCKS, Thomas, Wilhelm [DE/DE]; Salierallee 54, D-52066 Aachen (DE). ZWARTS, Jacobus [NL/NL]; Carmenlaan 5, NL-3438 VA Nieuwegein (NL). VAN WINDEN, Johannes, Albertus [NL/NL]; Molenwal 4, NL-3421 CM Oudewater (NL). RINSMA, Andries, Christian [NL/NL]; Leidseweg 73, NL-3531 BE Utrecht (NL). GURKA, Jiri [AT/AT]; Penz 290, A-4441 Behamberg (AT).		Published With international search report.	

(54) Title: SCREW ACTUATOR, AND BRAKE CALLIPER COMPRISING SUCH ACTUATOR



(57) Abstract

A screw actuator comprises a housing (17), a motor (7), an actuating member (10) and a screw mechanism (5) which provides a linear movement of the actuating member with respect to the housing in response to a rotational movement of the motor, which screw mechanism comprises a screw (11), a nut (14) engaging each other by rolling elements (13), one of said screw and nut being rotatably supported with respect to the housing, and a reduction gear means (6). The nut is fixed with respect to the housing, and the screw is rotatably supported with respect to the housing by means of the rolling elements.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LJ	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Screw actuator, and brake calliper comprising such actuator

The invention is related to a screw actuator, comprising an actuating member and a screw mechanism having a screw, nut and rolling elements, one of which screw
5 and nut is rotatably supported with respect to the housing and providing a linear movement of the actuating member with respect to the housing in response to a rotational movement of the motor, and a reduction gear means.

Such screw actuator is known from WO-A-9603301. Said known screw actuator comprises a screw mechanism which is supported with respect to the housing
10 by means of a bearing capable of accommodating axial and/or radial loads, e.g. an axial thrust bearing for accommodating the axial forces exerted on the brakepads.

This screw mechanism is a so-called roller screw mechanism. Depending on the application condition constraints i.e. space available, and load, one can select a roller screw or a ball screw type actuator. Specific application considerations for a
15 roller screw is that such roller screw mechanism provides a high power density, which means that within specific dimensional constraints, a relatively high load carrying capacity can be provided. Said carrying capacity however is predominantly related to axial loads. With respect to radial loads, the carrying capacity is less favourable compared to a ball screw. A roller screw mechanism is in general more
20 sensitive with respect to radial loads and misalignment.

Another specific component in a roller screw mechanism is the cage which is necessary to space the rollers. In high speed applications this cage mass results in higher starting torques.

The object of the invention is to provide an improved actuator. This object is
25 achieved in that the nut is fixed with respect to the housing, and the screw is rotatably supported with respect to the housing by means of the rolling elements. Said rolling elements may comprise rollers or balls.

In order to obtain about the same load bearing capacity as in a roller screw mechanism, the pitch diameter of the rolling balls, the ball diameter and its contact
30 angle with screw and nut, and the number of turns should be designed such that appropriate dimensions and the required load carrying capacity are provided. However, as the rolling elements of the screw mechanism can also act as bearing elements for supporting the rotating screw, no separate bearing is necessary to take

up the axial load. As a result, the overall dimensions for a ball screw mechanism may remain limited in order to meet application requirements.

The ball screw mechanism is less sensitive with respect to radial loads, which makes it less vulnerable for misalignments. Also, no cage is needed for recirculation
5 of the balls. Instead, recirculation of the balls may be obtained by means of recirculation tube or hole plug between the first and the last ball row or for each ball turn.

The axial moving and rotating screw according to the invention may be driven by the reduction gear means through a coupling means which allows axial
10 displacements. Said coupling means may comprise a drive shaft accommodated within a bore in the screw, the surface of the drive shaft and the bore having axial grooves which engage each other through balls or splines.

The screw may engage the actuating member through a bearing capable to cope with radial and axial load in order to stop the rotating motion in relation to the
15 moving actuating member.

The reduction gear means is preferably contained in a reduction gear module and the screw mechanism is contained in a screw mechanism module.

The actuating member may be executed as a piston, which is slidably held within a cylinder space of the housing. Said piston can be held non-rotatably by
20 means of a groove and pin assembly. The motor drive module can be mounted in-line with the actuator or in angled position.

For a right angle position of the motor module, the reduction gear means may comprise one or more reduction steps with at least part of a planetary gear system having a stationary outer ring gear wheel with inwardly pointing gear teeth. In
25 particular, the reduction gear means may comprise satellite gear wheels which mesh with the ring gear wheel and which are accommodated on a carrier connected to a rotary shaft engaging the screw mechanism, and the sun gear wheel of the planetary gear system may be accommodated on a drive shaft of the drive module. This system provides an optimal axial compactness of the application.

30 The sun gear wheel of the reduction gear means is connected to an angled or right angle gear reduction e.g. a bevel gear which mates with a motor driven bevel pinion. Said sun gear wheel and the bevel gear are carried out as a unitary gear wheel which is supported with respect to the nut of the screw mechanism by means

of a rolling element bearing. In order to achieve an appropriate reduction, the pitch diameter of the bevel gear is larger than the pitch diameter of the sun gear wheel.

Furthermore, a sensor fixed on a bearing or near the motorshaft may be provided for detecting rotational and/or translational movements of the screw mechanism or other operating parameters. Also, control means may be provided, said control means having an input for a control signal, e.g. from a brake pedal, and being connected to the sensor for controlling the electric motor on the basis of the control signal and the signal from the sensor. The sensor is in particular suitable for obtaining force feedback, wear compensation and/or maintenance indication.

The actuator according to the invention can be applied for different purposes. In particular, the actuator is suitable for use in a brake calliper for an electrically actuatable disc brake, said calliper comprising an actuator as described before, and a claw piece carrying two opposite brake pads, said actuator comprising a screw and a nut one of which is rotatably supported with respect to the housing by means of an angular bearing, and a reduction gear means.

The invention will further be described with reference to the embodiments of figures 1 and 2.

Figure 1 shows a brake calliper, comprising an actuator according to the invention, in exploded view.

Figure 2 shows the brake calliper according to figure 1, in assembled state.

Figure 3 shows a detail.

Figure 4 shows a detail of the ball screw.

Figure 5 shows a further embodiment.

The brake calliper shown in figures 1 and 2 comprises a claw piece 1 carrying a fixed brake pad 2 and a displaceable brake pad 3. Said brake pads 2, 3 can be brought into co-operation with brake disc 4.

The displaceable brake pad 3 engages a ball screw mechanism 5 which by means of reduction gear means 6 is driven by motor 7. Said motor 7 may be provided with a sensor 40, connected to the motor shaft.

More in particular, the displaceable brake pad 3 is connected by means of bolt 8 and screwthreaded hole 9 to an actuating member 10. Said actuating member 10 engages the screw 11 by means of an bearing 12 capable to take up axial load. Said

actuating member is carried out as a piston 10, which is slidably, but non-rotatably held in a cylinder space 38 in the housing 17.

By means of balls 13, screw 11 engages the nut 14. Said nut 14 has an external screwthread 15, by means of which the nut 14 is connected to the housing 17. Moreover, a recirculating tube 18 for recirculating the balls 13 upon rotating the screw 11 with respect to said nut 14, extends through the nut.

The screw 11 has a bore 37 with internal grooves 19, which engage balls 20. Said balls 20 also engage the external grooves 21 of drive shaft 22.

By rotating drive shaft 22 through reduction gear means 6 and motor 7, the screw 11 is rotated as well. As a result, it is displaced backward or forward by the co-operation of its screw type groove 23 with the screw type groove 24 of the nut 14, by means of the balls 15.

Drive shaft 23 is connected to a carrier 25, which carries satellite gear wheels 26. Said satellite gear wheels 26 each engage a ring gear wheel 27 as well as a sun gear wheel 28.

Sun gear wheel 28 forms a unity with bevel gear 29 which together form a unitary gear wheel 30. Said unitary gear wheel 30 by means of bearing 31 is supported with respect to the nut 14.

The bevel gear 29 engages the bevel pinion 31, which in turn is driven by motor 7.

The bearing 31, which supports the unitary gear wheel with respect to the nut 14, comprises a sensor 33 for detecting the rotations of the screw mechanism, and thereby the displacement of the displaceable brake pad 3.

Housing 17 comprises a bore 34, through which a wire can be guided to the outside from said sensor 33.

The carrier 25 is supported with respect to the housing 17 by means of bearing 35; by means of bolts 36, motor 7 is connected to said housing 17.

According to the detail of figure 3, the connection between brake pad 3 and piston 10 may alternatively be obtained through edges 43 which are slidable mounted in grooves 43 of piston 10.

In order to accommodate the axial forces exerted on the ball screw mechanism when applying a brake force on the brake pads 2,3, the screw threads 23, 24 of screw 11 respectively nut 14 can be adapted according to the embodiment shown in figure

4. In cross-section, the threads 23 have raised parts 51, whereas the threads 24 have raised parts 52.

As a result of these shapes, the working lines 50 as defined by the contact angles and the ball conformity with the ball tracks, which define the load paths which
5 play a role in force transfer, are in a more inclined position. The contact angle is between 45-70° in order to create optimized load carrying capacity for the ball screw in relation to the applied load specification.

The embodiment of figure 5 comprises a motor 61, having a stator 53 and a rotor 54 connected to a sleeve 55. The sleeve 55 is connected through the
10 intermediate piece 56 to drive shaft 22. Alternatively, the sleeve 55 may be connected to the drive shaft 22 through a gear reduction.

Drive shaft 22 drives screw 11 of screw mechanism 5, through the groove 21, 19 in the respectively the drive shaft 22 and the screw 11, as well as through the balls 20 accommodated in said grooves 21, 19.

15 Via thrust bearing 69, the screw 11 can be connected to e.g. a brake pad in case of an actuator applied in a claw piece. The thrust bearing 69 comprises two rings 67, 68, and balls 12. One of the rings 67 may form a unity with the screw 11. The other ring 68 may comprise a locking groove 66 for locking a brake pad (not shown) thereto.

20 The screw 11 is rotatably and translatably held in a cylinder space 59 defined by insert ring 58 inserted in nut 14 of the screw mechanism 5. Nut 14 and screw 11 of screw mechanism 5 engage each other through balls 13, accommodated in respective screwthreaded threads of nut 14 and screw 11.

Sleeve 55 connected to rotor 54 of motor 61 is rotatably supported on the
25 fixed nut 14 by means of bearings 63. These bearings have an outer race accommodated in the sleeve 55, and an inner ring 57 having appropriate raceways as well. The inner ring 57 is locked by means of locking ring 65. Furthermore, these bearings 63 have balls 64.

Alternatively, two separate standard ball or roller bearings may be applied.

30 The housing of the actuator is indicated by reference number 62.

Claims

1. Screw actuator, comprising a housing (17), a motor (7), an actuating member (10) and a screw mechanism (5) which provides a linear movement of the actuating member with respect to the housing in response to a rotational movement of the motor (7), which screw mechanism (5) comprises a screw (11), a nut (14) engaging each other by rolling elements (13), one of said screw (11) and nut (14) being rotatably supported with respect to the housing (17), and a reduction gear means (6), characterized in that the nut (14) is fixed with respect to the housing (17), and the screw (11) is rotatably supported with respect to the housing by means of the rolling elements (13).

2. Actuator according to claim 1, wherein the screw (11) is rotationally driven by the reduction gear means (6) through a coupling means (19-22) which allows axial displacements.

3. Actuator according to claim 2, wherein the coupling means comprises a shaft (22) accommodated within a bore (37) in the screw (11), the surface of the shaft (22) and bore having axial grooves (19, 21) which engage each other through balls (20).

4. Actuator according to any of the preceding claims, wherein the reduction gear means (6) is contained in a reduction gear module and the screw mechanism (5) is contained in a screw mechanism module.

5. Actuator according to claim 4, wherein the reduction gear means (6) comprises at least two gear reduction steps.

6. Actuator according to claim 6, wherein the reduction gear means comprises gear reduction steps of a different type, such as a planetary gear reduction step (25-28) and a right angle gear reduction step (28-31).

7. Actuator according to any of the preceding claims, wherein the screw (11) engages the actuating member (10) through a bearing (12) capable to carry axial and/or radial load.

5 8. Actuator according to any of claims 1-6, wherein the screw (11) is rigidly connected to the actuating member (10).

9. Actuator according to any of the preceding claims, wherein the actuating member is a piston (10), which is slidably held within a cylinder space (38, 59) of
10 the housing (17).

10. Actuator according to claim 7 and 9, wherein the piston (10) is held non-rotatably by means of a groove and pin assembly, or by means of a ball/groove assembly.

15 11. Actuator according to claims 8 and 9, wherein the piston (10) is rotatably held within the cylinder space (38).

12. Actuator according to claim 9, wherein the cylinder space (59) is formed
20 in the nut (14).

13. Actuator according to claim 4, wherein the modules are axially aligned.

14. Actuator according to claim 4, wherein the modules are in laterally shifted
25 positions.

15. Actuator according to any of the preceding claims, wherein one or two laterally shifted motors are provided.

30 16. Actuator according any of the preceding claims 4-15, wherein the reduction gear means (6) comprises at least part of a planetary gear system having a stationary outer ring gear (27) with inwardly pointing gear teeth.

17. Actuator according to claim 16, wherein the reduction gear means comprises satellite gear wheels (26) which mesh with the ring gear (27) and which are accommodated on a carrier (25) connected to the shaft (22) engaging the screw mechanism (15).

5

18. Actuator according to claim 17, wherein the sun gear wheel (28) of the reduction gear means (6) is connected to a bevel gear (29) which mates with a motor gear, e.g. an angled or right angled gear transmission (32).

10

19. Actuator according to claim 18, wherein the sun gear wheel (28) and the bevel gear (29) are carried out as a unitary gear wheel (30) which is supported with respect to the nut (14) of the screw mechanism (5) by means of a rolling element bearing (31).

15

20. Actuator according to claim 18 or 19, wherein the pitch diameter of the bevel gear (29) is larger than the pitch diameter of the sun gear wheel (28).

21. Actuator according to any of the preceding claims, wherein a sensor (33) is provided for detecting rotational and/or translational movements of the screw mechanism (5).

20

22. Actuator according to claim 21, wherein control means are provided, said control means having an input for a control signal, e.g. from a brake pedal, and being connected to the sensor (33) for controlling the electric motor (7) on the basis of the control signal and the signal from the sensor (33).

25

23. Actuator according to claim 22, wherein the control device is arranged for providing a maintenance indication signal.

30

24. Actuator according to any of the preceding claims, wherein balls or rollers (13) of the screw mechanism (5) are coated so as to maintain the proper function of the screw (11) under dry-running conditions such as a diamond-like carbon coating.

25. Actuator according to any of the preceding claims, wherein the motor (7) is an electric motor.

26. Actuator according to any of claims 1-24, wherein the motor (7) is a
5 hydraulic motor.

27. Actuator according to any of claims 1-24, wherein the motor (7) is a pneumatic motor.

10 28. Actuator according to any of the preceding claims, wherein at least one of the screw, nut, rolling elements and/or reduction gear components is obtained by hard turning.

29. Actuator according to any of the preceding claims, wherein the screw
15 mechanism comprises rolling balls, and the grooves in the screw and nut are arranged for adapted contact angles in view of improved axial load bearing capacity.

30. Reduction gear module for use in the actuator according to any of claims
2-27.

20

31. Screw mechanism module for use in the actuator according to any of claims 2-27.

32. Drive module for use in the actuator according to any of claims 2-29.
25

33. Brake calliper for an electrically actuatable disc brake, said calliper comprising an actuator according to any of the preceding claims 1-29, and a claw piece (1) carrying two opposite brake pads (2, 3), said actuator comprising a screw mechanism (5) the screw (11) of which is rotatably supported with respect to the
30 housing (17) by means of the balls (23) of the screw mechanism (5), a reduction gear means (6) and a motor (7).

34. Continuously variable transmission comprising two pulleys which each have two discs enclosing a V-shaped groove, as well as a belt engaging said grooves, the discs of each pulley being movable towards and away from each other so as to continually change the running radius of the belt, wherein the discs of each pulley are
5 displaceable by means of an actuator according to any of claims 1-29.

35. Continuously variable transmission according to claim 34, wherein the drive of the discs comprises hydraulic means.

10 36. Continuously variable transmission according to claim 34, wherein the drive of the discs comprises mechanical means.

37. Clutch, comprising two clutch plates which can be brought into frictional engagement for transferring a drive couple, said clutch plates being connected to the
15 shaft, comprising an actuator according to any of claims 1-29, said actuator having a hollow screw which accommodates one of the shafts.

1/4





fig-2



3/4

fig-3




fig-4





fig-5



INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 99/00303

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 F16D65/16 F16H25/22 F16H61/38 B60T13/74		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 F16D F16H B60T H02K		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 199 097 A (LORAL CORPORATION) 29 June 1988 (1988-06-29) page 13, line 7 - page 14, line 7; figure 4	1, 15, 21, 25, 33
A	EP 0 275 783 A (BENDIX FRANCE) 27 July 1988 (1988-07-27) column 5, line 43 - column 11, line 57; figures 1-5	1-3, 15, 21, 22, 25, 33
A	GB 2 291 949 A (ROTORK CONTROLS LTD) 7 February 1996 (1996-02-07) page 4, line 25 - page 13, line 11; figures 1-3	1-3, 9
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search <div style="text-align: center; font-weight: bold;">23 August 1999</div>		Date of mailing of the international search report <div style="text-align: center; font-weight: bold;">30/08/1999</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer <div style="text-align: center; font-weight: bold;">Hartevelde, C</div>

INTERNATIONAL SEARCH REPORT

Inter. Patent Application No

PCT/NL 99/00303

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 582 307 A (AISIN AW CO) 9 February 1994 (1994-02-09) column 5, line 16 - column 6, line 14; figure 1 ---	1,34
A	US 2 988 609 A (VERNON EVANS JR) 13 June 1961 (1961-06-13) column 3, line 14 - line 50; figures 2-5 ---	1,4
A	DE 195 11 287 A (ITT AUTOMOTIVE EUROPE) 25 January 1996 (1996-01-25) the whole document & WO 96 03301 A cited in the application -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Application No

PCT/NL 99/00303

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2199097 A	29-06-1988	US 4865162 A FR 2608241 A	12-09-1989 17-06-1988
EP 0275783 A	27-07-1988	FR 2610053 A JP 1021229 A JP 2586920 B KR 9511159 B US 4809824 A	29-07-1988 24-01-1989 05-03-1997 28-09-1995 07-03-1989
GB 2291949 A	07-02-1996	AT 167730 T DE 69503136 D DE 69503136 T EP 0770193 A ES 2117430 T WO 9604494 A JP 10507808 T NO 964417 A US 5865272 A	15-07-1998 30-07-1998 01-04-1999 02-05-1997 01-08-1998 15-02-1996 28-07-1998 17-10-1996 02-02-1999
EP 0582307 A	09-02-1994	JP 6058385 A DE 69301875 D DE 69301875 T US 5378198 A	01-03-1994 25-04-1996 26-09-1996 03-01-1995
US 2988609 A	13-06-1961	NONE	
DE 19511287 A	25-01-1996	CZ 9600594 A WO 9603301 A EP 0728089 A HU 75406 A PL 313522 A SK 29496 A US 5829557 A	17-07-1996 08-02-1996 28-08-1996 28-05-1997 08-07-1996 01-10-1996 03-11-1998